

Emergency

Draycote Emergency Twin Spot 4W 6500K IP65 Black E-SEL3 Emergency



5 YR
Product
Warranty



50,000
LED Lifespan
L70



Class
II



IP65
Ingress
Protection



Loop in
Loop out



Professionally
Replaceable



Professionally
Replaceable



Push-Fit
Terminals

LiFePO4 battery, Polycarbonate body and diffuser, Non maintained, 20mm conduit entry, Loop in / Loop out terminals



General Data

Technology

LED

Mounting options

Wall

Install Options

20mm Conduit Entry (Side, Base and Rear)

Electrical Connector Type

Push fit terminal

Input Electrical Connection

Neutral | Live

General Application

Commercial | Industrial | Educational

Operating Temperature Range °C

0 - +30

Warranty (Years)

5

Optical Data

LED Manufacturer / Type	BMTC 2835
Fixture Luminous Flux (Lm)	600 in Emergency
Luminaire Efficacy @6000K (lm/W)	600lm in Emergency
LOR %	100
Colour Selectable	No
Beam Angle°	40
Photobiological Risk Group	RG0

Light Source Data

Colour Temperature (K)	6500
Light Colour	Daylight
CRI Ra	>80

Electrical Data

Wattage (W)	4W Emergency
Mains voltage (V)	220 - 240
Lamp power factor	>0.5
Electrical protection	Class II
Control Gear Type CC or CV	Constant Current
Dimmable	No
Driver Brand	Lumineux
Nominal Frequency (Hz)	50 60

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
-------------------------------------	-------

Emergency Data

Battery Type	LiFePO4 3.2V
Battery Capacity (mAh)	7200mAh
Battery Warranty (Years)	5
Recharge Time (Hours)	24 Hours
Emergency Type	Non-Maintained
Test Procedure	E-SEL3 Self Test Manual
Emergency Duration (Hours)	3
Emergency Output	600

Physical Data

Housing Colour	White RAL9016
Body Material	Polycarbonate
IP Rating	65
IK Rating	8
Diffuser Material	Polycarbonate
Diffuser Finish	Frosted
Nominal Product Length (mm)	265
Nominal Product Width (mm)	90
Nominal Product Height (mm)	240
Weight (kg)	0.87

Standards and Approvals

Manufactured In Accordance To	EN60598-2-22 IEC62034
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate of Conformity	Available on Request
Accredited Members	LIA, ISO9001