

Emergency

Fontburn Emergency Exit Sign 3.5W 6000K White E-SEL3 Emergency



General Data

Mounting options	Ceiling Wall
Install Options	20mm Cut Out
Electrical Connector Type	Push fit terminal
Input Cable	0.75-2.5mm ²
Input Electrical Connection	Neutral P Live
General Application	Commercial Industrial Educational
Operating Temperature Range °C	0 - +30
Warranty (Years)	5

Optical Data

Fixture Luminous Flux (Lm)	110
Luminaire Efficacy @6000K (lm/W)	110
LOR %	100
Photobiological Risk Group	RG0

Light Source Data

Colour Temperature (K)	6000
Light Colour	Daylight

Electrical Data

Wattage (W)	3.5 Maintained 0.4 Emergency
Mains voltage (V)	220 - 240
Electrical protection	Class II
Driver Output Current (mA)	50
Control Gear Type CC or CV	Constant Current
Driver Brand	Lumineux
Nominal Frequency (Hz)	50 60

Emergency Data

Battery Type	LiFeP04 3.2V
Battery Capacity (mAh)	1500mAh
Recharge Time (Hours)	24 Hours
Emergency Type	Maintained Non-Maintained
Test Procedure	E-SEL3 Self Test Manual
Emergency Duration (Hours)	3
Emergency Output	50

Physical Data

Housing Colour	White
Body Material	Polycarbonate
IP Rating	20
Nominal Product Length (mm)	339
Nominal Product Width (mm)	42
Nominal Product Height (mm)	245

Standards and Approvals

Manufactured In Accordance To	EN60598-2-22 IEC 62034
--------------------------------------	------------------------