


EVO FRAME LED PANEL 600X600 POWER & CCT SWITCHABLE 30/36/40W 3000/3600/4000LM 3000/4000/6000K 100LM/W IP20 IK02 NON-DIMM 3 YEAR WARRANTY



Add a wow factor to retail, hospitality and office settings with the Evo Frame 600x600 LED Panel. A sleek, edge-lit lighting solution designed for modern indoor spaces, the Evo Frame Panel fits seamlessly into drop ceilings, allowing ceiling tiles to be fitted inside the frame for a clean, finished look. This creates a stylish "frame effect" around the ceiling tile, offering a unique and visually appealing lighting solution for otherwise utilitarian spaces. Offering adjustable wattage (30/36/40W) and colour temperature (3000K, 4000K, 6000K), this panel allows you to tailor the light output to suit different environments. Its long lifespan (up to 30,000 hours) ensures minimal maintenance, making it both cost-effective and reliable. With a 3 year warranty and simple installation, the Evo Frame Panel is a versatile and durable choice for any commercial lighting needs.

Details

Category:	Panels
Range Name:	Evo Frame
Product Type:	600 x 600
Product Body Finish:	Matt white
Market Segment:	Commercial indoor
Warranty (Years):	3

Physical Data

Product Length (mm):	595
Product Depth (mm):	15
Product Width (mm):	595
Product Weight (g):	300
Optic:	TP(a) rated Polycarbonate diffuser
Material:	Aluminium, Polycarbonate
Construction:	Aluminium frame, Polycarbonate diffuser
Cut Out Length (mm):	575
Cut Out Width (mm):	575
Luminaire Fixing:	Recessed in ceiling grid
Placement / Application:	Indoor, General Lighting

Electrical Data

Power (W):	30 / 36 / 40 (Power Switchable)
Power Consumption (W) :	30 / 36 / 40 (Power Switchable)
Power Factor:	0.9
Voltage Range (v):	220-240
Dimming:	Non-Dimmable
Driver Included:	Yes
Electric Current:	AC
EN:	EN-60598
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	3000 to 4000
Luminous efficacy (lm/W):	100
Correlated Colour Temperature (CCT) (K):	3000 / 4000 / 6000 (CCT Switchable)
Colour Temperature:	3000/4000/6000 - Warm White / Cool White / Daylight
Colour Temperature Name:	Warm White, Cool White, Daylight
Beam Angle:	120
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	30000
Lighting Method:	Back-lit
Switching Cycles:	25000

Environment

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
New Energy Rating:	E
Hg 0% (Mercury Free):	Yes
IP Rating (Back/Recessed side):	IP20
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-30
Maximum Operating Temperature (°C):	40
TP rating:	TP(a)

Packaging

Barcode:	5055788302964
Package Weight (g):	800
Package Length (mm):	620
Package Width (mm):	620
Package Depth (mm):	30

Light Source:	Non-replaceable
----------------------	-----------------



Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE