

FESTOON

110V EXTENDABLE FESTOONS

Our Connectable Festoon Kit range is now bigger and better, with the addition of 22m and 50m kits in addition to the original 12m kit. All feature our unique connector and can be joined together in any combination up to a maximum length of 200m. This makes extending the festoon on site simple and easy, saving time and money.



Features

- Extends festoons quickly and easily, up to a maximum combined length of 200m
- Avoids handling heavy, cumbersome festoons - simply link shorter and lighter kits together
- Unique Y-splitter cable for easy configuration, available to order separately
- New, higher light output LED heads
- Starter cable with pre-wired 110V 16A plug

Specification

Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
Festoon Kit Connectable 20-Way 50m	11000 lm		100W	110 lm/W

Product Information

Guarantee	2 Years
Colour Appearance (CCT)	6000K
IP Rating	IP44
IK Rating	IK07
Voltage	110V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra > 80

Colour Finish	Yellow
LED Life Expectancy	L70B50 35,000 Hours
Power Factor	0.9
Frequency	50Hz
Driver Type	Fixed Output
Approval	UKCA & CE
Electrical Class	Class I
Working Temperature	-20°C to 40°C


FESTOON

110V EXTENDABLE FESTOONS

Packaging Information

Dimensions (mm)	L: 50m Head: H; 60 x Ø: 75 mm
Product Net Weight (kg)	4.4 kg
Barcode	5055807624367
Box Dimensions (mm)	L: 340 x W: 340 x D: 160 mm
Box Gross Weight (kg)	9.4 kg

Units/Outer Carton	2
Outer Carton Barcode	15055807624364
Outer Carton Dimensions (mm)	L: 700 x W: 355 x D: 180 mm
Outer Carton Gross Weight (kg)	10.3 kg



ENERGY

FKF

A

B

C

D

E

F

G

E

30-100 kWh/1000h

5055807624364