

Modus Product Datasheet

Circular surface mounted or pendant downlight

Product Data

Warranty	5 years
Applications	Interior
Certification(s)	CE, RoHS

Physical Data

Colour Finish	Matt White (RAL 9016) Matt Black (RAL 9005)
Luminaire Fixing	Surface mounted, suspended
Construction Material	Aluminium
Diffuser Type	Glass-TPa rated
Unit Weight (kg)	1.55

Electrical Data

Wattage	14W 28W
Running Current	DC350mA DC750mA
Power Factor	>0.90
Voltage Range	AC220-240V
Inrush Current	<60A
Protection Class IEC	Class I

Performance Data


Efficacy	~110-113 Lm/W
Operating Temperature	-20°C to +45°C (0°C to 40°C for emergency)
*Kelvin	3000K 4000K
Beam Angle	60°
Operating Hours	>50000
CRI	>90 Ra
IP Rating	IP65
IK Rating	IK09
Macadam Ellipse	≤3 sdcM
L70 B50	100,000 hours
L80 B50	90,000 hours
L90 B50	42,000 hours
LEDs	Single bin Bridgelux COB

Contemporary design combined with IP65 protection



Wattage	*Kelvin	Lumens	Running Current
14W	3000K	1563	DC350mA
14W	4000K	1587	DC350mA
28W	3000K	3062	DC750mA
28W	4000K	3082	DC750mA

Dimensions (mm)



Modus Family



Light Distribution:

