

# Continuous Linear



Various Mounting Options



Wattage Switchable




1-10V Dimmable (as Standard)



Tri-Colour (3000K/4000K/5000K)

## Dimensions



# SpecLine

## Direct Linear



Power (Selectable)	Efficacy	Output	Kelvin
24W [Emergency 3W]	120Lm/cW	2880Lm [Emergency 360Lm]	Tri-Colour: 3000K, 4000K or 5000K
32W [Emergency 3W]	120Lm/cW	3840Lm [Emergency 360Lm]	
40W [Emergency 3W]	120Lm/cW	4800Lm [Emergency 360Lm]	

## Technical

Input Voltage	AC 200-240V
Colour Rendering Index	>80
Beam Spread	90°
Diffuser Type	Microprismatic
Operating Temp.	-20 to +45°C
Materials	Aluminium & Polycarbonate
IP Rating	IP20
Dimmable	1-10V (as Standard)
Dimensions	1200mm x 75mm x 60mm
Weight	2.57kg
MacAdam Step	<3
Emergency Output	3 Hours [3W]
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

**A T G E** Light Source Energy Rating

## Photometric Data

