



## BOL101 Post Light

Straight to mains IP54, 610lm post light

### Features

IP rating	IP54
IK rating	IK04
CSP Switchable	Single CCT
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	1.5Kg
Inrush Current	20A
Construction Material	Aluminium / PVC
UK Bathroom Zone	2
SELV	SELV
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	No

### Photometrics @ 25°C

Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
Black RAL9011	650mm	11W	3000K	360°	610	55	92	

### Wiring Information

Cable Required for Connector	3x 1.0mm <sup>2</sup>
Type of Wiring Required	Parallel

### LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (Integrated SLEV driver)	220-240V	Yes	No	2

### Accessories

JB5	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
-----	--	-----------------

11W

11W

IP54

IP54 ideal for walk ways and step lighting

360°

Benefiting from light all round with a 360° beam angle


### Guarantee

Warranty 5 years

### Features & benefits

- Straight to mains screw terminals
- Ideal for residential landscape projects, such as lighting low level shrubs
- Ideal to light up car parking spaces and driveways
- High lumen output of 610lm
- Great for soft illumination onto stone paths

Beam angle: 360°



Ø80mm

