

Continuous Linear



Various Mounting Options



Wattage Switchable




1-10 Dimmable (As Standard)




Tri-Colour (3000K/4000K/5000K)

Dimensions



Photometric Data



SpecLine

Direct Linear



Power (Selectable)	Efficacy	Output	Kelvin
60W (Emergency 3W)	120Lm/cW	7200Lm (Emergency 360Lm)	Tri-Colour: 3000K, 4000K or 5000K
80W (Emergency 3W)	120Lm/cW	9600Lm (Emergency 360Lm)	
100W (Emergency 3W)	120Lm/cW	12000Lm (Emergency 360Lm)	

Technical

Input Voltage	AC 200-240V
Colour Rendering Index	>80
Beam Spread	110°
Diffuser Type	Microprismatic
Operating Temp.	-20 to +45°C
Materials	Aluminium & Polycarbonate
IP Rating	IP20
Dimmable	1-10V (as Standard)
Dimensions	3000mm x 75mm x 60mm
Weight	6kg
MacAdam Step	<3
Emergency Output	3 Hours [3W]
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS