

LED CORN LAMP

Zero Maintenance Alternative



COMES WITH
DUST COVER
FOR EXTRA PROTECTION

3
YEAR
WARRANTY
WITH ONLINE
REGISTRATION

FEATURES:

- 110V - 240V - suitable for site lighting
- Wide range of wattages - 20W to 240W
- Light output up to 140lm per Watt
- 20W 125lm per Watt 100W / 120W 140lm per Watt
- Aluminium heat sink - no internal fan required
- Proven and constantly improved efficacy
- Robust aluminium and polycarbonate construction - IP64 rated
- Up to 73% energy saving payback from 14 months
- Easy to fit - no control gear required
- Our corn lamps are very efficient replacements for metal halide and
- High-pressure sodium (SON) lamps in all existing applications

APPLICATIONS



COMMERCIAL



COMMERCIAL
KITCHEN



FACTORIES



INDUSTRIAL



WAREHOUSE

LED CORN LAMP

Zero Maintenance Alternative

POWER	REPLACEMENT FOR	LUMENS	TEMP	CAP	DIMENSIONS (DIAMETER X LENGTH)
20W	70W	2,500	3000K	E27	60mm (D) x 148mm (L)
			4000K	E27	60mm (D) x 148mm (L)
			6000K	E27	60mm (D) x 148mm (L)
				E40	60mm (D) x 163mm (L)
30W	100W	3,900	3000K	E27	60mm (D) x 173mm (L)
			4000K	E27	60mm (D) x 173mm (L)
			6000K	E27	60mm (D) x 173mm (L)
				E40	60mm (D) x 188mm (L)
40W	150W	5,200	4000K	E40	85mm (D) x 216mm (L)
			6000K	E27	85mm (D) x 195 mm (L)
				E40	85mm (D) x 216mm (L)
60W	200W	7,800	4000K	E40	85mm (D) x 255mm (L)
			6000K	E40	85mm (D) x 255mm (L)
80W	250W	10,800	4000K	E40	130mm (D) x 255mm (L)
			6000K	E40	130mm (D) x 255mm (L)
100W	350W	14,000	4000K	F40	130mm (D) x 267mm (L)
			6000K	E40	130mm (D) x 267mm (L)
120W	400W	17,000	4000K	F40	130mm (D) x 288mm (L)
			6000K	E40	130mm (D) x 288mm (L)
150W	450W	20,000	6000K	E40	128mm (D) x 315mm (L)
200W	600W	25,800	6000K	E40	128mm (D) x 335mm (L)
240W	750W	34,800	6000K	F40	140mm (D) x 335mm (L)

BRIGHT SOURCE



Formerly rated A+
(same quality,
new energy rating
label regulations)



LED CORN LAMP

Zero Maintenance Alternative

LUX LEVEL TABLE

M	(Lx)	M	(Lx)	M	(Lx)
2	340	2	530	2	706
3	151	3	236	3	314
4	85	4	133	4	177
5	54	5	85	5	113
90° 20W					
2	1060	2	1467	2	1902
3	471	3	652	3	845
4	265	4	367	4	476
5	170	5	235	5	304
90° 60W					
2	2309	2	2717		
3	1026	3	1208		
4	577	4	679		
5	370	5	435		
90° 120W					
2	3505	2	4727		
3	1558	3	2101		
4	876	4	1182		
5	561	5	756		
90° 200W					
90° 30W					
90° 40W					
90° 80W					
90° 100W					
90° 150W					
90° 240W					

BRIGHT SOURCE



Formerly rated A+
(same quality,
new energy rating
label regulations)

